

# INSULCOAT 150FF AND 180 FF

European directive on Chemicals No. 1907/ 2006 (REACH) – products that are considered as articles are not compulsory in term of REACH regulation.

## 1. IDENTIFICATION OF THE SUBSTANCE AND OF THE COMPANY

Insulcoat 150 FF and 180 FF (Fiber Free) coating

### Identification of the suppliers

**INSULCON B.V.**

P.O. Box 134

**4650 AC STEENBERGEN, The Netherlands**

Zilverhoek 4, 4651 SP STEENBERGEN

Tel. : +31 (0)167-565750

Fax : +31 (0)167-566263

[www.insulcon.com](http://www.insulcon.com)

**KERAMAB N.V.**

Belgium

Tel. : + 32 (0)3 711.02.78

**INSULCON GmbH**

Germany

Tel.: + 49 (0)2131-408548-0

## 2. HAZARDS IDENTIFICATION

No particular hazards known.

## 3. COMPOSITION/INFORMATION ON INGREDIENTS

### Composition

Chemical composition: SiO<sub>2</sub> – 54-55% - Al<sub>2</sub>O<sub>3</sub> 40-44%, Fe<sub>2</sub>O<sub>3</sub> – 1-2%

## 4. FIRST AID MEASURES

### General

No special pre-cautions necessary

### In the event of splashes or contact with skin.

This product normally does not rinse the skin. If it does, wash immediately with plenty of water.

### After contact with eyes:

In case of contact with eyes rinse thoroughly with plenty of water.

### After inhaling

Supply fresh air

### After ingestion

When swallowed seek consult a physician.

Insulcon B.V.- The Netherlands - Tel: +31 (0)167 565 750

Insulcon GmbH - Germany - Tel: +49 (0)2131 408548-0

Keramab N.V. – Belgium - Tel: +32 (0)3 711 02 78

**INSULCON**

LEADER IN HIGH TEMPERATURE SOLUTIONS

**KERAMAB**

LEADER IN HIGH TEMPERATURE SOLUTIONS

[www.insulcon.com](http://www.insulcon.com) / [www.keramab.com](http://www.keramab.com)

Form: C4-022

Effective: 30072021/ES/ka

Supersedes:30112018/ES/ka

All Rights Reserved

# INSULCOAT 150FF AND 180 FF

## 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media. No special pre-cautions necessary

## 6. ACCIDENTAL RELEASE MEASURES

### **Environmental precautions:**

Avoid dust otherwise, no special pre-cautions necessary

## 7. HANDLING AND STORAGE

No special precautions necessary

### **Shelf life**

Approximately 12 months, based on unopened material kept in cool, dry storage conditions. Excessive heat will shorten shelf life and repeated freezing will damage the product. Storage between 5°C and 20°C is recommended.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ensure good ventilation, avoid dust.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

Form	: Paint
Color	: Off White / Grey / Black
Odor	: Odorless
Density	: 1.72 g/cm <sup>3</sup>
Solubility in water	: None

## 10. STABILITY AND REACTIVITY

### **Hazardous reactions:**

No hazardous reactions when stored and handled according to prescribed instructions.

## 11. TOXICOLOGICAL INFORMATION

No toxicological chronically effect, if used according to description.

# INSULCOAT 150FF AND 180 FF

## 12. EGOLOGICAL INFORMATION

No special precautions necessary

## 13. DISPOSAL CONSIDERATIONS

### **Product:**

Dispose of in accordance with local authority regulations

## 14. TRANSPORT INFORMATION

No special precautions necessary

## 15. REGULATORY INFORMATION

### **Labelling in accordance with EC-Directives:**

No label required according to EU-Directives

S-Phrases

S22

S25

## 16. OTHER INFORMATION

None